

LUNIO7 (Model)



IFORMATION <u>IES Files</u>	\downarrow
35W – 70W	
Up to 7200lm	
3000K – 4000K	
>80	
120-277V 60Hz / 0-10V	
> 60000h - L80 - B20 (Ta 25°C)	
Black - 12 / Dark bronze - 26 / Aluminium - 21 / Grey - 16	
	35W – 70W Up to 7200lm 3000K – 4000K >80 120-277V 60Hz / 0-10V > 60000h - L80 - B20 (Ta 25°C)

DESCRIPTION

Construction

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.

Electrical & Optics

- Universal input voltage: 120-277V 50/60Hz.
- 0-10V dimming available.
- Driver protected against voltage surges up to 6kV.
- Wiring on removable galvanized steel tray.
- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- PMMA lenses for LEDs.
- Screen made of 5/32" thermal-shock resistant tempered glass.

Listings

- UL certified to U.S. and Canadian standards, suitable for wet locations (cULus mark).
- Rated IP66 per EN60598.
- Luminaire rated for -40°C minimum ambient temperature.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Post-top installation (Ø 2" 3/8 tenon).
- Available wired with Zhaga Book 18 or NEMA ANSI C136.41 (5-pin) and waterproof cover. For the Zhaga Book 18 version add at the end of the code the suffix "ZU" for the version with adapter at the top, or "ZD" for the version with adapter at the bottom, or "ZB" for the version with adapter both at the top and at the bottom. For the NEMA ANSI C136.41 version, add the suffix "NU" at the end of the code for the version with adapter at














VERSIONS (Click on below link to configure your product)




<u>lunio7</u>

Ø 20" 15/32 24" 11/16

OPTICS





See accessories in the next page



TAPERED POLE COVER 3' D.BRONZE

Arcluce Code X-C003TCUS-26
Code Ref. 1099386X-26US



TECHNICAL INFORMATION

Color Dark bronze - 26

TAPERED POLE COVER 3' ALUM.

Arcluce Code X-C003TCUS-21
Code Ref. 1099386X-21US



TECHNICAL INFORMATION

Color Aluminium - 21

TAPERED POLE COVER 3' ANTH.

Arcluce Code X-CO03TCUS-16
Code Ref. 1099386X-16US



TECHNICAL INFORMATION

Color Grey - 16