

**NAPO** (Model)



**TECHNICAL INFORMATION**

[IES Files](#) 

Watt	0.4W – 4W
Luminaire	Up to 225lm
CCT	3000K – 4000K
CRI	>80
Wiring	24V
LED life time	> 60000h - L80 - B20 (Ta 25°C)
Color	White - 11 / Aluminium - 21

**DESCRIPTION**

**Construction**

- Turned aluminium body.
- Polyester powder paint resistant to UV rays.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.

**Electrical & Optics**

- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- Opal PMMA screen.
- To be operated only with constant voltage 24Vdc Class 2 remote drivers (order separately).

**Listings**

- UL certified to U.S. and Canadian standards, suitable for wet locations (cULus mark).
- Rated IP66 per EN60598.
- Luminaire rated for -40°C minimum ambient temperature.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

**Installation**

- Recessed installation.
- Steel spring clips.
- Supplied with power cord. 22AWG conductors.

IP66



**VERSIONS** *(Click on below link to configure your product)*



[with trim](#)

Size:  
Ø 2" 3/4  
2" 7/16

**OPTICS**

