

CONO (Model)



TECHNICAL INFORMATION

[IES Files](#) 

Watt	35W
Luminaire	Up to 5250lm
CCT	3000K – 4000K - DarkSky approved for CCTs of 3000K or lower
CRI	>80
Wiring	120-277V 60Hz / 0-10V
LED life time	> 60000h - L80 - B20 (Ta 25°C)
Color	Aluminium - 21 / Grey - 16

DESCRIPTION

Construction

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.

Electrical & Optics

- Universal input voltage: 120-277V 50/60Hz.
- 0-10V dimming available.
- Wiring on removable galvanized steel tray.
- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- PMMA lenses for LEDs.
- Screen made of 3/16" thermal-shock resistant tempered glass.

Listings

- UL certified to U.S. and Canadian standards, suitable for wet locations (cULus mark).
- Rated IP66 per EN60598.
- Luminaire rated for -40°C minimum ambient temperature.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.
- DarkSky approved for CCTs of 3000K or lower.

Installation

- Bracket installation (Ø60mm tenon).

IP66



VERSIONS *(Click on below link to configure your product)*



comfort


Size:
Ø 11" 13/16
13"



performance

Size:
Ø 11" 13/16
13"


OPTICS



See accessories in the next page

PAINTED DIE-CAST ALUMINIUM WALL BRACKET FOR Ø 60 MM ARM.


Arcluce Code **1099086X-21**
Code Ref.



TECHNICAL INFORMATION	
Color	Aluminium - 21
Weight	1.9 lb

PAINTED STEEL Ø 60 MM ARM.


Arcluce Code **1099067X-21**
Code Ref.



TECHNICAL INFORMATION	
Color	Aluminium - 21
Weight	15.65 lb

PAINTED DIE-CAST ALUMINIUM SINGLE POLE ATTACHMENT.


Arcluce Code **1099071X-21**
Code Ref.



TECHNICAL INFORMATION	
Color	Aluminium - 21
Weight	3.97 lb

PAINTED DIE-CAST ALUMINIUM DOUBLE POLE ATTACHMENT.


Arcluce Code **1099073X-21**
Code Ref.



TECHNICAL INFORMATION	
Color	Aluminium - 21
Weight	5.14 lb

DOUBLE POLE ATTACHMENT WITH CURVED ARMS IN PAINTED STEEL.


Arcluce Code **1099425X-21**
Code Ref.



TECHNICAL INFORMATION	
Color	Aluminium - 21
Weight	12.46 lb

SINGLE POLE ATTACHMENT WITH CURVED ARM IN PAINTED STEEL.


Arcluce Code **1099424X-21**
Code Ref.



TECHNICAL INFORMATION	
Color	Aluminium - 21
Weight	6.17 lb

PAINTED DIE-CAST ALUMINIUM WALL BRACKET FOR Ø 60 MM ARM.


Arcluce Code **1099086X-16**
Code Ref.



TECHNICAL INFORMATION	
Color	Grey - 16
Weight	1.9 lb

PAINTED STEEL Ø 60 MM ARM.


Arcluce Code **1099067X-16**
Code Ref.



TECHNICAL INFORMATION	
Color	Grey - 16
Weight	15.65 lb

POLE ATTACHMENT FOR 1 LIGHT FITTING.


Arcluce Code **1099071X-16**
Code Ref.



TECHNICAL INFORMATION	
Color	Grey - 16
Weight	3.97 lb

PAINTED DIE-CAST ALUMINIUM DOUBLE POLE ATTACHMENT.


Arcluce Code **1099073X-16**
Code Ref.



TECHNICAL INFORMATION	
Color	Grey - 16
Weight	5.14 lb

DOUBLE POLE ATTACHMENT WITH CURVED ARMS IN PAINTED STEEL.


Arcluce Code **1099425X-16**
Code Ref.



TECHNICAL INFORMATION	
Color	Grey - 16
Weight	12.46 lb

SINGLE POLE ATTACHMENT WITH CURVED ARM IN PAINTED STEEL.

Arcluce Code **1099424X-16**
Code Ref.



TECHNICAL INFORMATION	
Color	Grey - 16
Weight	6.17 lb