

CONO Catenary (Model)



TECHNICAL INFORMATION

[IES Files](#) 

Watt	35W
Luminaire	Up to 5250lm
CCT	3000K – 4000K - DarkSky approved for CCTs of 3000K or lower
CRI	
Wiring	>80
LED life time	> 60000h - L80 - B20 (Ta 25°C)
Color	Grey - 16 / Aluminium - 21

DESCRIPTION

Construction

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.

Electrical & Optics

- Universal input voltage: 120-277V 50/60Hz.
- 0-10V dimming available.
- Wiring on removable galvanized steel tray.
- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- PMMA lenses for LEDs.
- Screen made of 3/16" thermal-shock resistant tempered glass.

Listings

- UL certified to U.S. and Canadian standards, suitable for wet locations (cULus mark).
- DarkSky approved for CCTs of 3000K or lower.
- Rated IP66 per EN60598.
- Luminaire rated for -40°C minimum ambient temperature.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Catenary installation on passing cable Ø 15/32 max.
- Supplied with waterproof IP66 junction box with double M20 cable gland for through wiring.

IP66

IK08

CERTIFIED

0.97 ft²

VERSIONS (Click on below link to configure your product)



comfort



performance

Size:

Ø 11" 13/16

13"

18" 1/2

Size:

Ø 11" 13/16

13"

18" 1/2



OPTICS

