

# **DUEVENTI** (Model)



TECHNICAL INFORMATION		<u>IES Files</u> ↓
Watt	39W - 61W	
Luminaire	Up to 6750lm	
ССТ	3000K – 4000K	
CRI	>80	
Wiring	120-277V 60Hz / 0-10V	
LED life time	> 60000h - L80 - B20 (Ta 25°C)	
Color	Grey - 16 / Aluminium - 21	

## **DESCRIPTION**

#### Construction

- Die-cast aluminium body and trim (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Goniometer scale to aim light.

## **Electrical & Optics**

- Universal input voltage: 120-277V 50/60Hz.
- 0-10V dimming available.
- Driver protected against voltage surges up to 6kV.
- Wiring on removable galvanized steel tray.
- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- Reflector made of engineering plastic metalized in high-
- Screen made of 5/16" thermal-shock resistant tempered glass.

#### Listings

- UL certified to U.S. and Canadian standards, suitable for wet locations (cULus mark).
- Suitable for mounting within 1.2 m (4 ft) of ground.
- Rated IP66 per EN60598.
- Luminaire rated for -40°C minimum ambient temperature.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

#### Installation

- Surface installation.
- Die-cast aluminium base (EN 47100) for anchoring with rawlplugs.
- Supplied with power cord (18AWG conductors).









# VERSIONS (Click on below link to configure your product)





dueventi

dueventi compact

Size: Size: Size: 
Ø 8" 21/32 
Ø 8" 21/32 
16" 15/16 
9" 9/16 
9" 9/16

# **OPTICS**











See accessories in the next page



# ALUMINIUM HONEYCOMB LOUVRE WITH PAINTED STEEL EDGE.

Arcluce Code

1099111X-12

Code Ref.



## **TECHNICAL INFORMATION**

Color	Black - 12
Weight	0.07 lb

## PAINTED ALUMINIUM SLOPED VISOR.

Arcluce Code

1099199X-12

Code Ref.



## **TECHNICAL INFORMATION**

Color	Black - 12
Weight	0.07 lb

# AISI 316L STAINLESS STEEL PEG.

Arcluce Code

1099255X

Code Ref.



## **TECHNICAL INFORMATION**

Weight 1.76 lb

# PAINTED DIE-CAST ALUMINIUM SINGLE POLE ATTACHMENT (Ø 102 MM).

Arcluce Code

1099468X-16

Code Ref.



# **TECHNICAL INFORMATION**

Color	Grey - 16
Weight	3.31 lb



# PAINTED DIE-CAST ALUMINIUM DOUBLE POLE ATTACHMENT (Ø 102 MM).

Arcluce Code

1099469X-16

Code Ref.



## **TECHNICAL INFORMATION**

Color	Grey - 16
Weight	3.97 lb

# PAINTED DIE-CAST ALUMINIUM SINGLE POLE ATTACHMENT (Ø 102 MM).

Arcluce Code

1099468X-21

Code Ref.



## **TECHNICAL INFORMATION**

Color	Aluminium - 21
Weight	3.31 lb

# PAINTED DIE-CAST ALUMINIUM DOUBLE POLE ATTACHMENT (Ø 102 MM).

Arcluce Code

1099469X-21

Code Ref.



## **TECHNICAL INFORMATION**

Color	Aluminium - 21
Weight	3.97 lb