

# EMPHASIS (Model)



## TECHNICAL INFORMATION

<b>Watt</b>	41W – 68W
<b>Luminaire</b>	Up to 7000lm
<b>CCT</b>	3000K – 4000K
<b>CRI</b>	>80
<b>Wiring</b>	120-277V 60Hz / 0-10V
<b>LED life time</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>Color</b>	Aluminium - 21 / Grey - 16

## DESCRIPTION

### Construction

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.

### Electrical & Optics

- Universal input voltage: 120-277V 50/60Hz.
- 0-10V dimming available.
- Driver protected against voltage surges up to 10kV.
- Wiring on removable galvanized steel tray.
- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- Reflector made of anodized aluminium with non-iridescent specular finishing.
- Screen made of 15/32" thermal-shock resistant tempered glass.

### Listings

- UL certified to U.S. and Canadian standards, suitable for wet locations (cULus mark).
- Rated IP66 per EN60598.
- Luminaire rated for -40°C minimum ambient temperature.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

### Installation

- Wall mounted.
- Double cable gland M20 for through wiring.
- Die-cast aluminium base (EN 47100) for anchoring with rawlplugs.
- Supplied with power cord (18AWG conductors).
- For bidirectional versions, wiring in double switch.



## VERSIONS *(Click on below link to configure your product)*



[oneway](#)



[twoway](#)

Size:  
16" 17/32  
7" 23/32  
8" 1/16


Size:  
16" 17/32  
7" 23/32  
8" 1/16

## OPTICS



See accessories in the next page


## PAINTED DIE-CAST ALUMINIUM AND STEEL SINGLE POLE ATTACHMENT.

Arcluce Code **1099083X-21**Code Ref. **W8937-21****TECHNICAL INFORMATION**

<b>Color</b>	Aluminium - 21
--------------	----------------

<b>Weight</b>	5.51 lb
---------------	---------


## PAINTED DIE-CAST ALUMINIUM AND STEEL DOUBLE POLE ATTACHMENT.

Arcluce Code **1099001X-21**Code Ref. **W8940-21****TECHNICAL INFORMATION**

<b>Color</b>	Aluminium - 21
--------------	----------------

<b>Weight</b>	10.58 lb
---------------	----------


## PAINTED DIE-CAST ALUMINIUM AND STEEL SINGLE POLE ATTACHMENT.

Arcluce Code **1099083X-16**Code Ref. **W8937-16****TECHNICAL INFORMATION**

<b>Color</b>	Grey - 16
--------------	-----------

<b>Weight</b>	5.51 lb
---------------	---------

## PAINTED DIE-CAST ALUMINIUM AND STEEL DOUBLE POLE ATTACHMENT.

Arcluce Code **1099001X-16**Code Ref. **W8940-16****TECHNICAL INFORMATION**

<b>Color</b>	Grey - 16
--------------	-----------

<b>Weight</b>	10.58 lb
---------------	----------