

# FORMAT1 (Model)



## TECHNICAL INFORMATION

[IES Files](#) 

<b>Watt</b>	14W – 48W
<b>Luminaire</b>	Up to 5250lm
<b>CCT</b>	3000K – 4000K
<b>CRI</b>	>80
<b>Wiring</b>	120-277V 60Hz / 0-10V
<b>LED life time</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>Color</b>	Grey - 16 / Aluminium - 21

## DESCRIPTION

### Construction

- Die-cast aluminium body and trim (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- Goniometer scale to aim light.

### Electrical & Optics

- Universal input voltage: 120-277V 50/60Hz.
- 0-10V dimming available.
- Driver protected against voltage surges up to 5kV.
- Wiring on removable galvanized steel tray.
- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- PMMA lenses for LEDs.
- Screen made of 3/16" thermal-shock resistant tempered glass.

### Listings

- UL certified to U.S. and Canadian standards, suitable for wet locations (cULus mark).
- Suitable for mounting within 1.2 m (4 ft) of ground.
- Rated IP66 per EN60598.
- Luminaire rated for -25°C minimum ambient temperature.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

### Installation

- Surface installation.
- Galvanized and painted steel bracket.
- Supplied with power cord (18AWG conductors).

IP66



## VERSIONS *(Click on below link to configure your product)*


[format1](#)

Size:

9" 27/32


2" 15/16

19" 1/2


## OPTICS




See accessories in the next page

**PAINTED DIE-CAST ALUMINIUM SINGLE POLE ATTACHMENT (Ø60).**
**Arcluce Code      1099413X-16**
**Code Ref.**

**TECHNICAL INFORMATION**
**Color**                      Grey - 16


**Weight**                     3.2 lb

**PAINTED DIE-CAST ALUMINIUM DOUBLE POLE ATTACHMENT (Ø60).**
**Arcluce Code      1099414X-16**
**Code Ref.**

**TECHNICAL INFORMATION**
**Color**                      Grey - 16


**Weight**                     5.07 lb

**PAINTED STEEL FLOODLIGHT-SUPPORTING BRACKET, FOR Ø 60 MM POLE.**
**Arcluce Code      1099152X-16**
**Code Ref.**

**TECHNICAL INFORMATION**
**Color**                      Grey - 16


**Weight**                     17.64 lb

**PAINTED STEEL FLOODLIGHT-SUPPORTING BRACKET, FOR Ø 60 MM POLE.**
**Arcluce Code      1099153X-16**
**Code Ref.**

**TECHNICAL INFORMATION**
**Color**                      Grey - 16


**Weight**                     7.17 lb

**PAINTED DIE-CAST ALUMINIUM AND STEEL SINGLE POLE ATTACHMENT (Ø 102 MM).**
**Arcluce Code      1099470X-16**
**Code Ref.**

**TECHNICAL INFORMATION**
**Color**                      Grey - 16


**Weight**                     5.73 lb

**PAINTED DIE-CAST ALUMINIUM AND STEEL DOUBLE POLE ATTACHMENT (Ø 102 MM) .**
**Arcluce Code      1099471X-16**
**Code Ref.**

**TECHNICAL INFORMATION**
**Color**                      Grey - 16

**Weight**                     8.16 lb

**ADJUSTABLE POLE BRACKET FOR 1 LIGHT FITTING FOR Ø=76 MM POLE GREY, SIMILAR TO (RAL 7024)**
**Arcluce Code      1099514X-16**
**Code Ref.**

**TECHNICAL INFORMATION**
**Color**                      Grey - 16

**Weight**                     3.09 lb


**ADJUSTABLE POLE BRACKET FOR 2 LIGHT FITTINGS FOR Ø=76MM POLE - GREY, SIMILAR TO (RAL 7024)**
**Arcluce Code      1099515X-16**
**Code Ref.**

**TECHNICAL INFORMATION**
**Color**                      Grey - 16

**Weight**                     3.31 lb

## PAINTED DIE-CAST ALUMINIUM SINGLE POLE ATTACHMENT (Ø60).

Arcluce Code **1099413X-21**

Code Ref.

**TECHNICAL INFORMATION**


<b>Color</b>	Aluminium - 21
--------------	----------------

<b>Weight</b>	3.2 lb
---------------	--------

## PAINTED DIE-CAST ALUMINIUM DOUBLE POLE ATTACHMENT (Ø60).

Arcluce Code **1099414X-21**

Code Ref.

**TECHNICAL INFORMATION**


<b>Color</b>	Aluminium - 21
--------------	----------------

<b>Weight</b>	5.07 lb
---------------	---------

## PAINTED STEEL FLOODLIGHT-SUPPORTING BRACKET, FOR Ø 60 MM POLE.

Arcluce Code **1099152X-21**

Code Ref.

**TECHNICAL INFORMATION**


<b>Color</b>	Aluminium - 21
--------------	----------------

<b>Weight</b>	17.64 lb
---------------	----------

## PAINTED STEEL FLOODLIGHT-SUPPORTING BRACKET, FOR Ø 60 MM POLE.


Arcluce Code **1099153X-21**

Code Ref.


**TECHNICAL INFORMATION**

<b>Color</b>	Aluminium - 21
--------------	----------------


<b>Weight</b>	7.17 lb
---------------	---------

**PAINTED DIE-CAST ALUMINIUM AND STEEL SINGLE POLE ATTACHMENT (Ø 102 MM).**
**Arcluce Code      1099470X-21**
**Code Ref.**

**TECHNICAL INFORMATION**
**Color**                      Aluminium - 21


**Weight**                     5.73 lb

**PAINTED DIE-CAST ALUMINIUM AND STEEL DOUBLE POLE ATTACHMENT (Ø 102 MM) .**
**Arcluce Code      1099471X-21**
**Code Ref.**

**TECHNICAL INFORMATION**
**Color**                      Aluminium - 21

**Weight**                     8.16 lb

**ADJUSTABLE POLE BRACKET FOR 1 LIGHT FITTING FOR Ø=76 MM POLE -ALUMINIUM (RAL 9005)**
**Arcluce Code      1099514X-21**
**Code Ref.**

**TECHNICAL INFORMATION**
**Color**                      Aluminium - 21

**Weight**                     3.09 lb

**ADJUSTABLE POLE BRACKET FOR 2 LIGHT FITTINGS FOR Ø=76MM POLE - ALUMINIUM (RAL 9005)**
**Arcluce Code      1099515X-21**
**Code Ref.**

**TECHNICAL INFORMATION**
**Color**                      Aluminium - 21

**Weight**                     3.31 lb

---

**FORMAT ADJUSTABLE POLE ATTACHMENT Ø=60 GREY, SIMILAR TO (RAL 7024)**Arcluce Code **1099598X-16**

Code Ref.

**TECHNICAL INFORMATION**

<b>Color</b>	Grey - 16
--------------	-----------

---

<b>Weight</b>	1.76 lb
---------------	---------

---

---

**FORMAT ADJUSTABLE POLE ATTACHMENT Ø=60 ALUMINIUM (RAL 9005)**Arcluce Code **1099598X-21**

Code Ref.

**TECHNICAL INFORMATION**

<b>Color</b>	Aluminium - 21
--------------	----------------

---

<b>Weight</b>	1.76 lb
---------------	---------

---