

GOTHIC180 (Model)



TECHNICAL INFORMATION

[IES Files](#)

Watt	19W – 36W
Luminaire	Up to 1750lm
CCT	3000K – 4000K
CRI	>80
Wiring	
LED life time	> 60000h - L80 - B20 (Ta 25°C)
Color	Grey - 16 / Aluminium - 21

DESCRIPTION




VERSIONS *(Click on below link to configure your product)*



twoway	threeway	radial	radial - 24Vdc	twoway (Smart Functions)	threeway (Smart Functions)	radial (Smart Functions)
Size:	Size:	Size:	Size:	Size:	Size:	Size:
27" 15/16 to 39" 3/8	27" 15/16 to 39" 3/8	27" 15/16 to 39" 3/8	39" 3/8	39" 3/8	39" 3/8	39" 3/8
7" 3/32	7" 3/32	7" 3/32	7" 3/32	7" 3/32	7" 3/32	7" 3/32



OPTICS




See accessories in the next page

HOT DIPPED ZINC-COATED STEEL BASEMENT FOR GROUND ANCHORING.

Arcluce Code **1099093X**


Code Ref.

**TECHNICAL INFORMATION****Weight** 14.55 lb

ZINC-COATED AND PAINTED STEEL BASE PLATE WITH ZINC-COATED STEEL STUD BOLTS. 350 MM HIGH.

Arcluce Code **1099402X-16**

Code Ref.

**TECHNICAL INFORMATION****Color** Grey - 16**Weight** 3.09 lb


IP68 LINEAR JOINT - 2 WAYS - 2 POLES.

Arcluce Code **1099408X**

Code Ref.

**TECHNICAL INFORMATION****Weight** 0.07 lb


JUNCTION BOX IP68 - 4 WAYS - 2/3 POLES.

Arcluce Code **1099259X**Code Ref. **O7932****TECHNICAL INFORMATION****Weight** 0.11 lb

GALVANIZED AND PAINTED STEEL BASE PLATE WITH GALVANIZED STEEL STUD BOLTS. 350 MM HIGH.

Arcluce Code **1099402X-21**

Code Ref.

**TECHNICAL INFORMATION**

Color Aluminium - 21

Weight 3.09 lb

JUNCTION BOX IP68 - 4 WAYS - 4/5 POLES.

Arcluce Code **1099407X**

Code Ref.

**TECHNICAL INFORMATION**

Weight 0.18 lb

IP68 LINEAR JOINT - 2 WAYS - 4 POLES.

Arcluce Code **1099410X**

Code Ref.

**TECHNICAL INFORMATION**

Weight 0.07 lb