

INGROUND110 short (Model)



TECHNICAL INFORMATION

[IES Files](#) ↓

Watt	4W
Luminaire	Up to 575lm
CCT	3000K – RGBW
CRI	>80
Wiring	
LED life time	> 60000h - L80 - B20 (Ta 25°C), > h - L - B (Ta 25°C)
Color	Stainless Steel - 30

DESCRIPTION



VERSIONS *(Click on below link to configure your product)*



[round trim above the ground](#)

Size:
 Ø 4" 11/16
 2" 7/8
 7" 15/32



[squared trim above the ground](#)

Size:
 2" 7/8
 7" 15/32
 4" 23/32



[round trim flush with ground](#)

Size:
 Ø 4" 11/32
 2" 7/8
 7" 15/32




OPTICS



See accessories in the next page

THERMOPLASTIC MATERIAL RECESSED INSTALLATION BOX.

Arcluce Code **1099217X**Code Ref. **O7347****TECHNICAL INFORMATION****Weight** 0.31 lb


IP68 LINEAR JOINT - 2 WAYS - 2 POLES.

Arcluce Code **1099408X**


Code Ref.

**TECHNICAL INFORMATION****Weight** 0.07 lb

JUNCTION BOX IP68 - 4 WAYS - 2/3 POLES.

Arcluce Code **1099259X**Code Ref. **O7932****TECHNICAL INFORMATION****Weight** 0.11 lb

THERMOPLASTIC MATERIAL RECESSED INSTALLATION BOX WITH AISI 316L STAINLESS STEEL COUNTER-RING.

Arcluce Code **1099218X**Code Ref. **O7348****TECHNICAL INFORMATION****Weight** 0.53 lb

JUNCTION BOX IP68 - 4 WAYS - 4/5 POLES.

Arcluce Code **1099407X**

Code Ref.

**TECHNICAL INFORMATION****Weight** 0.18 lb

Arcluce Code **1098009X**

Code Ref.

**TECHNICAL INFORMATION****Weight** 1.1 lb

Arcluce Code **1098010X**

Code Ref.

**TECHNICAL INFORMATION****Weight** 1.1 lb
