

INGROUND110 short (Model)



TECHNICAL INFORMATION

[IES Files](#) 

Watt	4W
Luminaire	Up to 575lm
CCT	3000K – RGBW
CRI	>80
Wiring	
LED life time	> 60000h - L80 - B20 (Ta 25°C), > h - L - B (Ta 25°C)
Color	Stainless Steel - 30

DESCRIPTION



VERSIONS *(Click on below link to configure your product)*



[round trim above the ground](#)

Size:
Ø 4" 11/16
2" 7/8
7" 15/32



[squared trim above the ground](#)

Size:
2" 7/8
7" 15/32
4" 23/32



[round trim flush with the ground](#)

Size:
Ø 4" 11/32
2" 7/8
7" 15/32




OPTICS



See accessories in the next page

THERMOPLASTIC MATERIAL RECESSED INSTALLATION BOX.

Arcluce Code **1099217X**
Code Ref.



TECHNICAL INFORMATION

Weight 0.31 lb

IP68 LINEAR JOINT - 2 WAYS - 2 POLES.

Arcluce Code **1099408X**
Code Ref.




TECHNICAL INFORMATION

Weight 0.07 lb

JUNCTION BOX IP68 - 4 WAYS - 2/3 POLES.

Arcluce Code **1099259X**
Code Ref.




TECHNICAL INFORMATION

Weight 0.11 lb

THERMOPLASTIC MATERIAL RECESSED INSTALLATION BOX WITH AISI 316L STAINLESS STEEL COUNTER-RING.

Arcluce Code **1099218X**
Code Ref.



TECHNICAL INFORMATION

Weight 0.53 lb

JUNCTION BOX IP68 - 4 WAYS - 4/5 POLES.

Arcluce Code **1099407X**
Code Ref.



TECHNICAL INFORMATION

Weight 0.18 lb


Arcluce Code **1098009X**
Code Ref.



TECHNICAL INFORMATION

Weight 1.1 lb

Arcluce Code **1098010X**
Code Ref.



TECHNICAL INFORMATION

Weight 1.1 lb
