TECHNICAL INFORMATION



# INGROUND180 (Model)



TECHNICAL INFORMATION		<u>IES Files</u>
Watt	8W	
Luminaire	Up to 925lm	
ССТ	3000K – 4000K	
CRI	>80	
Wiring	120-277V 60Hz / 0-10V	
LED life time	> 60000h - L80 - B20 (Ta 25°C)	
Color	Stainless Steel - 30	

### **DESCRIPTION**

### Construction

- Die-cast aluminium body (EN 47100).
- AISI 316L stainless steel trim.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.

### **Electrical & Optics**

- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- PMMA lenses for LEDs.
- Screen made of 13/32" thermal-shock resistant tempered glass.

### Listings

- UL certified to U.S. and Canadian standards, suitable for wet locations (cULus mark).
- Rated IP67 per EN60598.
- Luminaire rated for -20°C minimum ambient.
- 5000Kg static load capacity per EN60598.
- Can be driven over at maximum speed 20Km/h per EN60598.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

#### Installation

- Recessed installation.
- Double cable gland PG13.5 for through wiring.
- Supplied with recessed installation box made of engineering plastic.
- Upon request fixtures can be supplied with anti-slip glass.











# **VERSIONS** (Click on below link to configure your product)



round trim flush with ground

Size: Ø 8" 11" 31/32



round trim above the ground

Size: Ø 7" 11/16 11" 27/32



squared trim above the ground

Size:

11" 27/32 to 11" 31/32

7" 3/4 to 8"

# OPTICS





See accessories in the next page



THERMOPLASTIC MATERIAL RECESSED INSTALLATION BOX WITH AISI 316L STAINLESS STEEL COUNTER-RING.

Arcluce Code 1099220X

Code Ref.



### **TECHNICAL INFORMATION**


Weight 1.98 lb

### ANTI-SLIP OPAL GLASS.

Arcluce Code

1099282X

Code Ref.



### **TECHNICAL INFORMATION**

Weight 1.21 lb

## THERMOPLASTIC MATERIAL RECESSED INSTALLATION BOX.

Arcluce Code 1099210X

Code Ref.



### **TECHNICAL INFORMATION**

Weight 1.1 lb