

INGROUND180 short (Model)



TECHNICAL INFORMATION


[IES Files](#) ↓

Watt	11W – 12W
Luminaire	Up to 1150lm
CCT	3000K – RGBW
CRI	>80
Wiring	
LED life time	> 60000h - L80 - B20 (Ta 25°C)
Color	Stainless Steel - 30

DESCRIPTION



VERSIONS *(Click on below link to configure your product)*



[round trim above the ground](#)

[squared trim above the ground](#)

Size:
 Ø 7" 11/16
 4" 13/16
 5" 5/16

Size:
 4" 13/16
 5" 5/16
 7" 3/4



OPTICS




See accessories in the next page

ANTI-SLIP OPAL GLASS.

Arcluce Code **1099282X**

Code Ref.



TECHNICAL INFORMATION

Weight 1.21 lb

THERMOPLASTIC MATERIAL RECESSED INSTALLATION BOX.

Arcluce Code **1099208X**

Code Ref.




TECHNICAL INFORMATION

Weight 0.44 lb

PAINTED STEEL GLARE-CONTROL LOUVRED.

Arcluce Code **1099324X**

Code Ref.



TECHNICAL INFORMATION

Weight 1.32 lb

IP68 LINEAR JOINT - 2 WAYS - 3 POLES.

Arcluce Code **1099409X**

Code Ref.




TECHNICAL INFORMATION

Weight 0.07 lb

JUNCTION BOX IP68 - 4 WAYS - 2/3 POLES.

Arcluce Code **1099259X**

Code Ref.

**TECHNICAL INFORMATION****Weight** 0.11 lb

JUNCTION BOX IP68 - 4 WAYS - 4/5 POLES.

Arcluce Code **1099407X**

Code Ref.

**TECHNICAL INFORMATION****Weight** 0.18 lb

Arcluce Code **1098009X**

Code Ref.

**TECHNICAL INFORMATION****Weight** 1.1 lb

Arcluce Code **1098010X**

Code Ref.

**TECHNICAL INFORMATION****Weight** 1.1 lb
