

INGROUND260 (Model)



TECHNICAL INFORMATION

[IES Files](#) ↓

| | |
|----------------------|--|
| Watt | 14W – 20W |
| Luminaire | Up to 2000lm |
| CCT | 3000K – 4000K |
| CRI | >80 |
| Wiring | 120-277V 60Hz / 0-10V, 120-277V 60Hz / DALI, 120V 60Hz |
| LED life time | > 100000h - L80 - B20 (Ta 25°C) |
| Color | Stainless Steel - 30 |

DESCRIPTION

Construction

- Die-cast aluminium body (EN 47100).
- AISI 316L stainless steel trim.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.

Electrical & Optics

- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- Reflector made of engineering plastic metalized in high-vacuum.
- Screen made of 19/32" thermal-shock resistant tempered glass.

Listings

- Intertek certified to U.S. and Canadian standards suitable for wet locations (ETL mark).
- Rated IP67 per EN60598.
- Luminaire rated for -20°C minimum ambient.
- 6000Kg static load capacity per EN60598.
- Can be driven over at maximum speed 20Km/h per EN60598.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Recessed installation.
- Double cable gland PG16 for through wiring.
- Supplied with recessed installation box made of engineering plastic.
- Upon request fixtures can be supplied with anti-slip glass.

IP67



VERSIONS *(Click on below link to configure your product)*



[round trim above the ground](#)

Size:
Ø 10" 13/16
16" 3/8



[squared trim above the ground](#)

Size:
16" 3/8

10" 13/16

OPTICS




See accessories in the next page

GLASS LENS FOR ELLIPTIC BEAM.

Arcluce Code **1099253X**


Code Ref.

**TECHNICAL INFORMATION****Weight** 0.6 lb

ANTI-SLIP OPAL GLASS.

Arcluce Code **1099283X**

Code Ref.

**TECHNICAL INFORMATION****Weight** 3.59 lb

THERMOPLASTIC MATERIAL RECESSED INSTALLATION BOX.

Arcluce Code **1099211X**


Code Ref.

**TECHNICAL INFORMATION****Weight** 2.2 lb

PAINTED DIE-CAST ALUMINIUM DIRECTIONAL LOUVRE FOR GLARE CONTROL.

Arcluce Code **1099110X-12**

Code Ref.


**TECHNICAL INFORMATION****Color** Black - 12

Weight 0.51 lb

PAINTED DIE-CAST ALUMINIUM GLARE-CONTROL LOUVRED.

Arcluce Code **1099108X-12**

Code Ref.



TECHNICAL INFORMATION

Color Black - 12

Weight 0.4 lb
