

INGROUND90 (Model)



TECHNICAL INFORMATION		<u>IES Files</u> ↓
Watt	4W – 12W	
Luminaire	Up to 1600lm	
ССТ	3000K – 4000K	
CRI	>80	
Wiring	24Vcd, 350mA	
LED life time	> 60000h - L80 - B20 (Ta 25°C)	
Color	Stainless Steel - 30	

DESCRIPTION

Construction

- AISI 316L stainless steel body and trim.
- Silicone rubber gaskets.

Electrical & Optics

- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- PMMA lenses for LEDs.
- Screen made of 5/16" thermal-shock resistant tempered

Listings

- UL certified to U.S. and Canadian standards, suitable for wet locations (cULus mark).
- Rated IP68 per EN60598.
- Luminaire rated for -40°C minimum ambient temperature.
- 1000Kg static load capacity per EN60598.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.





Installation

- Recessed installation.
- Supplied with recessed installation box made of engineering
- Other recessed installation boxes made of engineering plastic or of AISI 316L stainless steel available.
- Supplied with power cord. 22AWG conductors.

VERSIONS (Click on below link to configure your product)



trim flush with ground, constant current

Ø 3" 29/32 5" 9/32



trim flush with ground, constant voltage

Ø 3" 29/32 5" 9/32



trim above the ground, constant current

Size: Ø 4" 13/32

5" 9/32 7" 15/32



trim above the ground, constant voltage

Size: Ø 4" 13/32 5" 9/32

7" 15/32



OPTICS















See accessories in the next page



THERMOPLASTIC MATERIAL RECESSED INSTALLATION BOX.

Arcluce Code

1099330X

Code Ref.



TECHNICAL INFORMATION

Weight 0.44 lb

THERMOPLASTIC MATERIAL RECESSED INSTALLATION BOX.

Arcluce Code

1099331X

Code Ref.



TECHNICAL INFORMATION

Weight 0.33 lb

PAINTED ALUMINIUM HONEYCOMB LOUVRE. TO BE ORDERED TOGETHER WITH THE LUMINAIRE.

Arcluce Code

1099341X-12

Code Ref.



TECHNICAL INFORMATION

Color Black - 12

Weight 0.11 lb