

INTIS (Model)



IFORMATION	<u>IES Files</u> ↓
41W	
Up to 4450lm	
3000K – 4000K	
>80	
120-277V 60Hz / 0-10V	
> 60000h - L80 - B20 (Ta 25°C)	
Grey - 16 / Aluminium - 21	
	41W Up to 4450lm 3000K - 4000K >80 120-277V 60Hz / 0-10V > 60000h - L80 - B20 (Ta 25°C)

DESCRIPTION

Construction

- Die-cast aluminium body and trim (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.

Electrical & Optics

- 0-10V dimming available.
- Driver protected against voltage surges up to 6kV.
- Wiring on removable galvanized steel tray.
- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- Reflector made of engineering plastic metalized in highvacuum.
- Screen made of 5/32" thermal-shock resistant tempered glass

Listings

- UL certified to U.S. and Canadian standards, suitable for wet locations (cULus mark).
- Rated IP66 per EN60598.
- Luminaire rated for -40°C minimum ambient temperature.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Suspended installation.
- Die-cast aluminium base (EN 47100) for anchoring with rawlplugs.
- Universal plate for mounting on standard junction boxes.
- Supplied with power cord (18AWG conductors).







VERSIONS (Click on below link to configure your product)



suspended

Size: Ø 8" 5/16 8" 21/32

OPTICS





