

KOMPASS Bollard (Model)



TECHNICAL INFORMATION		<u>IES Files</u> ↓
Watt	4W – 30W	
Luminaire	Up to 425lm	
ССТ	3000K – 4000K	
CRI	>80	
Wiring	120-277V 60Hz	
LED life time	> 60000h - L80 - B20 (Ta 25°C)	
Color	Aluminium - 21 / Grey - 16	

DESCRIPTION

Construction

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.

Electrical & Optics

- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- Screen made of 5/16" thermal-shock resistant tempered glass.

Listings

- UL certified to U.S. and Canadian standards, suitable for wet locations (cULus mark).
- Suitable for mounting within 1.2 m (4 ft) of ground.
- Rated IP66 per EN60598.
- Luminaire rated for -20°C minimum ambient.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Surface installation.
- Die-cast aluminium base (EN 47100) for anchoring with rawlplugs.











VERSIONS (Click on below link to configure your product)







 Size:
 Size:

 5" 29/32
 5" 29/32

 4" 1/32
 4" 1/32

OPTICS

comfort+

