

# KOMPASS Bollard (Model)



## TECHNICAL INFORMATION

[IES Files](#) ↓

<b>Watt</b>	4W – 30W
<b>Luminaire</b>	Up to 425lm
<b>CCT</b>	3000K – 4000K
<b>CRI</b>	>80
<b>Wiring</b>	120-277V 60Hz
<b>LED life time</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>Color</b>	Aluminium - 21 / Grey - 16

## DESCRIPTION

### Construction

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.

### Electrical & Optics

- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- Screen made of 5/16" thermal-shock resistant tempered glass.

### Listings

- UL certified to U.S. and Canadian standards, suitable for wet locations (cULus mark).
- Suitable for mounting within 1.2 m (4 ft) of ground.
- Rated IP66 per EN60598.
- Luminaire rated for -20°C minimum ambient.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.


### Installation

- Surface installation.
- Die-cast aluminium base (EN 47100) for anchoring with rawlplugs.


IP66



## VERSIONS *(Click on below link to configure your product)*



[comfort+](#)



[comfort](#)

Size:  
5" 29/32  
4" 1/32  
19" 11/32 to 42" 13/32

Size:  
5" 29/32  
4" 1/32  
19" 11/32 to 42" 13/32

## OPTICS

