

KRANE (Model)



TECHNICAL INFORMATION

[IES Files](#)

Watt	40W – 80W
Luminaire	Up to 5900lm
CCT	3000K – 4000K
CRI	>80
Wiring	120-277V 60Hz / 0-10V
LED life time	> 60000h - L80 - B20 (Ta 25°C)
Color	Grey - 16 / Aluminium - 21

DESCRIPTION

Construction

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.

Electrical & Optics

- 0-10V dimming available.
- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- PMMA lenses for LEDs.
- Screen made of 5/16" thermal-shock resistant tempered glass.

Listings

- UL certified to U.S. and Canadian standards, suitable for wet locations (cULus mark).
- Rated IP66 per EN60598.
- Luminaire rated for -20°C minimum ambient.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Post-top installation (Ø 2" 3/8 tenon).

IP66



VERSIONS *(Click on below link to configure your product)*



[single light fitting](#)




[double light fitting](#)

Size:
37" 13/32
11" 21/32
4" 1/32

Size:
63"
11" 21/32
4" 1/32

OPTICS



See accessories in the next page

TAPERED POLE COVER 3' ANTH.

Arcluce Code **X-CO03TCUS-16**

Code Ref. **1099386X-16US**



TECHNICAL INFORMATION

Color Grey - 16

TAPERED POLE COVER 3' ALUM.

Arcluce Code **X-CO03TCUS-21**

Code Ref. **1099386X-21US**



TECHNICAL INFORMATION

Color Aluminium - 21
