

# KRANE (Model)



## TECHNICAL INFORMATION

[IES Files](#)

<b>Watt</b>	40W – 80W
<b>Luminaire</b>	Up to 5900lm
<b>CCT</b>	3000K – 4000K
<b>CRI</b>	>80
<b>Wiring</b>	120-277V 60Hz / 0-10V
<b>LED life time</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>Color</b>	Grey - 16 / Aluminium - 21

## DESCRIPTION

### Construction

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.

### Electrical & Optics

- 0-10V dimming available.
- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- PMMA lenses for LEDs.
- Screen made of 5/16" thermal-shock resistant tempered glass.

### Listings

- UL certified to U.S. and Canadian standards, suitable for wet locations (cULus mark).
- Rated IP66 per EN60598.
- Luminaire rated for -20°C minimum ambient.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

### Installation

- Post-top installation (Ø 2" 3/8 tenon).

IP66



## VERSIONS *(Click on below link to configure your product)*



[single light fitting](#)



[double light fitting](#)

Size:  
37" 13/32  
11" 21/32  
4" 1/32

Size:  
63"  
11" 21/32  
4" 1/32

## OPTICS



See accessories in the next page

TAPERED POLE COVER 3' ANTH.

Arcluce Code **X-CO03TCUS-16**  
Code Ref. **1099386X-16US**



**TECHNICAL INFORMATION**

**Color** Grey - 16

---

TAPERED POLE COVER 3' ALUM.

Arcluce Code **X-CO03TCUS-21**  
Code Ref. **1099386X-21US**



**TECHNICAL INFORMATION**

**Color** Aluminium - 21

---