


# KRION-IN short Step Lights

(Model)



## TECHNICAL INFORMATION

[IES Files](#)

<b>Watt</b>	6W – 41W
<b>Luminaire</b>	Up to 450lm
<b>CCT</b>	3000K – 4000K
<b>CRI</b>	>80
<b>Wiring</b>	CV 24V REM-D
<b>LED life time</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>Color</b>	Grey - 16 / Aluminium - 21

## DESCRIPTION

### Construction

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.

### Electrical & Optics

- Universal input voltage: 120-277V 50/60Hz.
- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- Screen made of 5/16" thermal-shock resistant tempered glass.

### Listings

- UL certified to U.S. and Canadian standards, suitable for wet locations (cULus mark).
- Rated IP67 per EN60598.
- Luminaire rated for -20°C minimum ambient.
- 1000Kg static load capacity per EN60598.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.


### Installation

- Recessed installation.
- Steel spring clips.
- Supplied with extruded aluminium recessed box.
- End caps to be ordered separately (1099390X).

IP67



## VERSIONS *(Click on below link to configure your product)*



[comfort](#)

Size:

2" 23/32

3" 11/16

13" 5/8 to 48" 7/32

## OPTICS



See accessories in the next page

## SUCTION CUP FOR DEVICE REMOVAL (1 PIECE).

Arcluce Code **1099068X**

Code Ref.

**TECHNICAL INFORMATION****Weight** 0.04 lb

---

## STRAIGHT JOINT.

Arcluce Code **1099241X**

Code Ref.


**TECHNICAL INFORMATION****Weight** 0.02 lb

---

## PAINTED EXTRUDED ALUMINIUM INSTALLATION-BOX

Arcluce Code **1099382X-16**

Code Ref.

**TECHNICAL INFORMATION****Color** Grey - 16

---


**Weight** 0.99 lb

---

## PAINTED STEEL END CAPS (2 PCS).

Arcluce Code **1099390X-16**

Code Ref.

**TECHNICAL INFORMATION****Color** Grey - 16


---

**Weight** 0.66 lb


---

**PAINTED EXTRUDED ALUMINIUM INSTALLATION-BOX**Arcluce Code **1099382X-21**


Code Ref.

**TECHNICAL INFORMATION****Color** Aluminium - 21**Weight** 0.99 lb**PAINTED STEEL END CAPS (2 PCS).**Arcluce Code **1099390X-21**


Code Ref.

**TECHNICAL INFORMATION****Color** Aluminium - 21**Weight** 0.66 lb**PAINTED EXTRUDED ALUMINIUM INSTALLATION-BOX**Arcluce Code **1099383X-16**

Code Ref.


**TECHNICAL INFORMATION****Color** Grey - 16**Weight** 1.87 lb**PAINTED EXTRUDED ALUMINIUM INSTALLATION-BOX**Arcluce Code **1099383X-21**

Code Ref.


**TECHNICAL INFORMATION****Color** Aluminium - 21**Weight** 1.87 lb

**PAINTED EXTRUDED ALUMINIUM INSTALLATION-BOX**Arcluce Code **1099384X-16**

Code Ref.

**TECHNICAL INFORMATION****Color** Grey - 16**Weight** 3.64 lb**PAINTED EXTRUDED ALUMINIUM INSTALLATION-BOX**Arcluce Code **1099384X-21**

Code Ref.

**TECHNICAL INFORMATION****Color** Aluminium - 21**Weight** 3.64 lb