

KUBIX180 (Model)



TECHNICAL INFORMATION

[IES Files](#) 

Watt	18W – 36W
Luminaire	Up to 1650lm
CCT	3000K – 4000K
CRI	>80
Wiring	
LED life time	> 60000h - L80 - B20 (Ta 25°C)
Color	Grey - 16 / Aluminium - 21

DESCRIPTION



VERSIONS *(Click on below link to configure your product)*



[two-way](#)



[three-way](#)



[radial](#)




[radial - 24Vdc](#)

Size:	Size:	Size:	Size:
19" 11/16 to 39" 3/8	19" 11/16 to 39" 3/8	19" 11/16 to 39" 3/8	39" 3/8
7" 3/32	7" 3/32	7" 3/32	7" 3/32




OPTICS



See accessories in the next page

HOT DIPPED ZINC-COATED STEEL BASEMENT FOR GROUND ANCHORING.


Arcluce Code **1099093X**
Code Ref.



TECHNICAL INFORMATION	
Weight	14.55 lb

ZINC-COATED AND PAINTED STEEL BASE PLATE WITH ZINC-COATED STEEL STUD BOLTS. 350 MM HIGH.

Arcluce Code **1099402X-16**
Code Ref.



TECHNICAL INFORMATION	
Color	Grey - 16
Weight	3.09 lb

IP68 LINEAR JOINT - 2 WAYS - 2 POLES.


Arcluce Code **1099408X**
Code Ref.



TECHNICAL INFORMATION	
Weight	0.07 lb

JUNCTION BOX IP68 - 4 WAYS - 2/3 POLES.


Arcluce Code **1099259X**
Code Ref.



TECHNICAL INFORMATION	
Weight	0.11 lb

GALVANIZED AND PAINTED STEEL BASE PLATE WITH GALVANIZED STEEL STUD BOLTS. 350 MM HIGH.

Arcluce Code **1099402X-21**
Code Ref.



TECHNICAL INFORMATION	
Color	Aluminium - 21
Weight	3.09 lb

Arcluce Code **1099770X**
Code Ref.

TECHNICAL INFORMATION	
Weight	0.44 lb

JUNCTION BOX IP68 - 4 WAYS - 4/5 POLES.

Arcluce Code **1099407X**
Code Ref.



TECHNICAL INFORMATION	
Weight	0.18 lb

IP68 LINEAR JOINT - 2 WAYS - 4 POLES.

Arcluce Code **1099410X**
Code Ref.



TECHNICAL INFORMATION	
Weight	0.07 lb