


MIKO Bollard (Model)



TECHNICAL INFORMATION

[IES Files](#) ↓

Watt	20W
Luminaire	Up to 1800lm
CCT	3000K – 4000K - DarkSky approved for CCTs of 3000K or lower
CRI	>80
Wiring	120-277V 60Hz / 0-10V
LED life time	> 60000h - L80 - B20 (Ta 25°C)
Color	Grey - 16 / Aluminium - 21 / Black - 12

DESCRIPTION

Construction

- Die-cast aluminium body (EN 47100).
- Extruded aluminium pole.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.

Electrical & Optics

- Universal input voltage: 120-277V 50/60Hz.
- 0-10V dimming available.
- Wiring on removable galvanized steel tray.
- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- PMMA lenses for LEDs.
- Screen made of 3/16" thermal-shock resistant tempered glass.

Listings

- DarkSky approved for CCTs of 3000K or lower.
- Intertek certified to U.S. and Canadian standards suitable for wet locations (ETL mark).
- Suitable for mounting within 1.2 m (4 ft) of ground.
- Rated IP66 per EN60598.
- Luminaire rated for -30°C minimum ambient.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Surface installation.
- Die-cast aluminium base (EN 47100) for anchoring with rawlplugs.
- Supplied with steel base plate and j-shaped anchor bolts.
- Available on request zinc-plated steel pillar for reinforced anchoring.
- Supplied with power cord (18AWG conductors).

IP66



VERSIONS *(Click on below link to configure your product)*



[miko](#)

Size:
 Ø 7" 7/8
 3"
 11" 13/16 to 39" 3/8

OPTICS




See accessories in the next page

HOT-DIPPED ZINC-COATED STEEL BASEMENT FOR GROUND ANCHORING.

Arcluce Code **1099334X**

Code Ref.

**TECHNICAL INFORMATION**


Color	Chrome - 31
--------------	-------------

Weight	3.75 lb
---------------	---------

HOT-DIPPED ZINC-COATED STEEL BASEMENT FOR GROUND ANCHORING WITH A HOT-DIPPED ZINC-COATED STEEL POLE INTERNAL REINFORCEMENT.

Arcluce Code **1099335X**

Code Ref.

**TECHNICAL INFORMATION**


Color	Chrome - 31
--------------	-------------

Weight	3.31 lb
---------------	---------

ZINC-COATED STEEL SPIKE.

Arcluce Code **1099339X**

Code Ref.


**TECHNICAL INFORMATION**

Weight	0.55 lb
---------------	---------

HOT-DIPPED ZINC-COATED STEEL BASEMENT FOR GROUND ANCHORING WITH A HOT-DIPPED ZINC-COATED STEEL POLE INTERNAL REINFORCEMENT.

Arcluce Code **1099336X**

Code Ref.

**TECHNICAL INFORMATION**


Color	Chrome - 31
--------------	-------------

Weight	5.07 lb
---------------	---------

HOT-DIPPED ZINC-COATED STEEL BASEMENT FOR GROUND ANCHORING WITH A HOT-DIPPED ZINC-COATED STEEL POLE INTERNAL REINFORCEMENT.

Arcluce Code **1099337X**

Code Ref.



TECHNICAL INFORMATION


Color Chrome - 31

Weight 6.39 lb

HOT-DIPPED ZINC-COATED STEEL BASEMENT FOR GROUND ANCHORING WITH A HOT-DIPPED ZINC-COATED STEEL POLE INTERNAL REINFORCEMENT.

Arcluce Code **1099338X**

Code Ref.



TECHNICAL INFORMATION

Color Chrome - 31

Weight 7.72 lb