

NAPO (Model)



TECHNICAL INFORMATION		<u>IES Files</u> ↓
Watt	0.4W – 4W	
Luminaire	Up to 225lm	
ССТ	3000K – 4000K	
CRI	>80	
Wiring	24V	
LED life time	> 60000h - L80 - B20 (Ta 25°C)	
Color	Aluminium - 21 / White - 11	

DESCRIPTION

Construction

- Turned aluminium body.
- Polyester powder paint resistant to UV rays.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.

Electrical & Optics

- To be operated only with constant voltage 24Vdc Class 2 remote drivers (order separately).
- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- Opal PMMA screen.

Listings

- UL certified to U.S. and Canadian standards, suitable for wet locations (cULus mark).
- Rated IP66 per EN60598.
- Luminaire rated for -40°C minimum ambient temperature.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Recessed installation.
- Steel spring clips.
- Supplied with power cord. 22AWG conductors.

IP66





VERSIONS (Click on below link to configure your product)



with trim

Size: Ø 2" 3/4 2" 7/16

OPTICS

