

# NAPO (Model)



## TECHNICAL INFORMATION

[IES Files](#) 

|                      |                                |
|----------------------|--------------------------------|
| <b>Watt</b>          | 0.4W – 4W                      |
| <b>Luminaire</b>     | Up to 225lm                    |
| <b>CCT</b>           | 3000K – 4000K                  |
| <b>CRI</b>           | >80                            |
| <b>Wiring</b>        | 24V                            |
| <b>LED life time</b> | > 60000h - L80 - B20 (Ta 25°C) |
| <b>Color</b>         | White - 11 / Aluminium - 21    |

## DESCRIPTION

### Construction

- Turned aluminium body.
- Polyester powder paint resistant to UV rays.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.

### Electrical & Optics

- To be operated only with constant voltage 24Vdc Class 2 remote drivers (order separately).
- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- Opal PMMA screen.

### Listings

- UL certified to U.S. and Canadian standards, suitable for wet locations (cULus mark).
- Rated IP66 per EN60598.
- Luminaire rated for -40°C minimum ambient temperature.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.



### Installation

- Recessed installation.
- Steel spring clips.
- Supplied with recessed installation box made of engineering plastic.
- Supplied with power cord. 22AWG conductors.

IP66



## VERSIONS *(Click on below link to configure your product)*


[trimless](#)

[with trim](#)

Size:  
 Ø 1" 31/32  
 3" 15/16  
 0" 5/8

Size:  
 Ø 2" 3/4  
 3" 15/16  
 0" 25/32

## OPTICS




See accessories in the next page

THERMOPLASTIC MATERIAL RECESSED INSTALLATION BOX.

Arcluce Code **1099226X**

Code Ref.



**TECHNICAL INFORMATION**

**Weight** 0.13 lb

---