

NAPO (Model)



TECHNICAL INFORMATION

[IES Files](#) 

| | |
|---------------|--------------------------------|
| Watt | 0.4W – 4W |
| Luminaire | Up to 225lm |
| CCT | 3000K – 4000K |
| CRI | >80 |
| Wiring | 24V |
| LED life time | > 60000h - L80 - B20 (Ta 25°C) |
| Color | White - 11 / Aluminium - 21 |

DESCRIPTION

Construction

- Turned aluminium body.
- Polyester powder paint resistant to UV rays.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.

Electrical & Optics

- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- Opal PMMA screen.
- To be operated only with constant voltage 24Vdc Class 2 remote drivers (order separately).

Listings

- UL certified to U.S. and Canadian standards, suitable for wet locations (cULus mark).
- Rated IP66 per EN60598.
- Luminaire rated for -40°C minimum ambient temperature.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.


Installation

- Recessed installation.
- Steel spring clips.
- Supplied with recessed installation box made of engineering plastic.
- Supplied with power cord. 22AWG conductors.

IP66




VERSIONS *(Click on below link to configure your product)*



[trimless](#)

Size:
Ø 1" 31/32
3" 15/16
0" 5/8



[with trim](#)

Size:
Ø 2" 3/4
3" 15/16
0" 25/32


OPTICS



See accessories in the next page

THERMOPLASTIC MATERIAL RECESSED INSTALLATION BOX.

Arcluce Code **1099226X**
Code Ref.



TECHNICAL INFORMATION

| | |
|---------------|---------|
| Weight | 0.13 lb |
|---------------|---------|