

# NAPO (Model)



TECHNICAL INFORMATION		<u>IES Files</u> ↓
Watt	0.4W - 4W	
Luminaire	Up to 225lm	
ССТ	3000K – 4000K	
CRI	>80	
Wiring	24V	
LED life time	> 60000h - L80 - B20 (Ta 25°C)	
Color	White - 11 / Aluminium - 21	

## **DESCRIPTION**

#### Construction

- Turned aluminium body.
- Polyester powder paint resistant to UV rays.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.

### **Electrical & Optics**

- To be operated only with constant voltage 24Vdc Class 2 remote drivers (order separately).
- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- Opal PMMA screen.

### Listings

- UL certified to U.S. and Canadian standards, suitable for wet locations (cULus mark).
- Rated IP66 per EN60598.
- Luminaire rated for -40°C minimum ambient temperature.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

### Installation

- Recessed installation.
- Steel spring clips.
- Supplied with recessed installation box made of engineering plastic.
- Supplied with power cord. 22AWG conductors.

# IP66





# **VERSIONS** (Click on below link to configure your product)





# trimless with trim

 Size:
 Size:

 Ø 1" 31/32
 Ø 2" 3/4

 3" 15/16
 3" 15/16

 0" 5/8
 0" 25/32

# **OPTICS**



See accessories in the next page



# THERMOPLASTIC MATERIAL RECESSED INSTALLATION BOX.

Arcluce Code

1099226X

Code Ref.



## **TECHNICAL INFORMATION**

Weight 0.13 lb