


PIXOL110 (Model)



TECHNICAL INFORMATION		<u>IES Files</u>
Watt	6W – 14W	
Luminaire	Up to 1650lm	
ССТ	3000K – 4000K	
CRI	>80	
Wiring		
LED life time	> 60000h - L80 - B20 (Ta 25°C)	
Color	Aluminium - 21 / Grey - 16 / White - 11 / Corten - 23	

DESCRIPTION



IP66

VERSIONS (Click on below link to configure your product)





3" 15/16

4" 11/32









Siz

4" 11/32	
3" 15/16	
4" 11/32	



performance (twoway)

performance+ (oneway) Size: 4" 11/32 3" 15/16

4" 11/32





OPTICS

Size:








































ADAPTER PLATE FOR INSTALLATION ON ELECTRICAL BOXES.

Arcluce Code

1099622X

Code Ref.



TECHNICAL INFORMATION

Weight 1.1 lb


BASE PLATE FOR WALL/CEILING APPLICATION FOR SIDE ENTRY OF POWER CABLE - ALUMINIUM (RAL

9005).

Arcluce Code

1099647X-21

Code Ref.



TECHNICAL INFORMATION


Color	Aluminium - 21
Weight	1.76 lb

BASE PLATE FOR WALL/CEILING APPLICATION FOR SIDE ENTRY OF POWER CABLE - ALUMINIUM (RAL 9005).

Arcluce Code

1099647X-16

Code Ref.



TECHNICAL INFORMATION


Color	Grey - 16
Weight	1.76 lb

BASE PLATE FOR WALL/CEILING APPLICATION FOR SIDE ENTRY OF POWER CABLE - ALUMINIUM (RAL 9005).

Arcluce Code

1099647X-11

Code Ref.



TECHNICAL INFORMATION


Color	White - 11
Weight	1.76 lb



BASE PLATE FOR WALL/CEILING APPLICATION FOR SIDE ENTRY OF POWER CABLE - ALUMINIUM (RAL 9005).

Arcluce Code 1099647X-23

Code Ref.



TECHNICAL INFORMATION

Color	Corten - 23
Weight	1.76 lb