


PIXOL150 (Model)



TECHNICAL IN	IFORMATION <u>IES Files</u>
Watt	7W – 31W
Luminaire	Up to 3400lm
ССТ	3000K – 4000K
CRI	>80
Wiring	
LED life time	> 60000h - L80 - B20 (Ta 25°C)
Color	White - 11 / Grey - 16 / Corten - 23 / Aluminium - 21

DESCRIPTION



IP66

VERSIONS (Click on below link to configure your product)









performance+ (twoway) Size:





performance (oneway)

Size:	
5" 29/32 3" 15/16 5" 29/32	



performance (twoway)





IK08

OPTICS














































ADAPTER PLATE FOR INSTALLATION ON ELECTRICAL BOXES.

Arcluce Code

1099622X

Code Ref.



TECHNICAL INFORMATION


Weight 1.1 lb

BASE PLATE FOR WALL/CEILING APPLICATION FOR SIDE ENTRY OF POWER CABLE - WHITE

Arcluce Code

1099626X-11

Code Ref.



TECHNICAL INFORMATION


Color	White - 11
Weight	1.76 lb

BASE PLATE FOR WALL/CEILING APPLICATION FOR SIDE ENTRY OF POWER CABLE - GREY, SIMILAR TO

(RAL 7024)

Arcluce Code 1099626X-16

Code Ref.



TECHNICAL INFORMATION


Color	Grey - 16
Weight	1.76 lb

BASE PLATE FOR WALL/CEILING APPLICATION FOR SIDE ENTRY OF POWER CABLE - CORTEN

Arcluce Code

1099626X-23

Code Ref.



TECHNICAL INFORMATION


Color	Corten - 23
Weight	1.76 lb



BASE PLATE FOR WALL/CEILING APPLICATION FOR SIDE ENTRY OF POWER CABLE - ALUMINIUM (RAL 9005)

Arcluce Code Code Ref.

1099626X-21



TECHNICAL INFORMATION

Color	Aluminium - 21
Weight	1.76 lb