


PIXOL150 (Model)



TECHNICAL INFORMATION

[IES Files](#) 

| | |
|---------------|---|
| Watt | 31W |
| Luminaire | Up to 3400lm |
| CCT | 3000K – 4000K |
| CRI | >80 |
| Wiring | 120-277V 60Hz 0-10V |
| LED life time | > 60000h - L80 - B20 (Ta 25°C) |
| Color | White - 11 / Grey - 16 / Aluminium - 21 |

DESCRIPTION

Construction

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.

Electrical & Optics

- Universal input voltage: 120-277V 50/60Hz.
- 0-10V dimming available.
- Wiring on removable galvanized steel tray.
- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- PMMA lenses for LEDs.
- Screen made of 3/16" thermal-shock resistant tempered glass.
- Driver protected against voltage surges up to 5kV.

Listings

- UL certified to U.S. and Canadian standards, suitable for wet locations (cULus mark).
- Rated IP66 per EN60598.
- Luminaire rated for -25°C minimum ambient temperature.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.


Installation

- Wall mounted.
- Die-cast aluminium base (EN 47100) for anchoring with rawlplugs.
- Universal plate for mounting on standard junction boxes (accessory).
- Spacer for side-entry of conduits (accessory).


IP66



VERSIONS *(Click on below link to configure your product)*



[oneway](#)



[twoway](#)

Size:

5" 29/32
3" 15/16
5" 29/32

Size:

5" 29/32
3" 15/16
5" 29/32


OPTICS



See accessories in the next page

ADAPTER PLATE FOR INSTALLATION ON ELECTRICAL BOXES.

Arcluce Code **1099622X**
Code Ref.




TECHNICAL INFORMATION

| | |
|--------|--------|
| Weight | 1.1 lb |
|--------|--------|

BASE PLATE FOR WALL/CEILING APPLICATION FOR SIDE ENTRY OF POWER CABLE - WHITE

Arcluce Code **1099626X-11**
Code Ref.




TECHNICAL INFORMATION

| | |
|--------|------------|
| Color | White - 11 |
| Weight | 1.76 lb |

BASE PLATE FOR WALL/CEILING APPLICATION FOR SIDE ENTRY OF POWER CABLE - GREY, SIMILAR TO (RAL 7024)

Arcluce Code **1099626X-16**
Code Ref.




TECHNICAL INFORMATION

| | |
|--------|-----------|
| Color | Grey - 16 |
| Weight | 1.76 lb |

BASE PLATE FOR WALL/CEILING APPLICATION FOR SIDE ENTRY OF POWER CABLE - ALUMINIUM (RAL 9005)

Arcluce Code **1099626X-21**
Code Ref.



TECHNICAL INFORMATION

| | |
|--------|----------------|
| Color | Aluminium - 21 |
| Weight | 1.76 lb |