

# PIXOL150 (Model)



TECHNICAL IN	IFORMATION <u>IES Files</u>	IES Files
Watt	31W	
Luminaire	Up to 3250lm	
ССТ	3000K – 4000K	
CRI	>80	
Wiring	120-277V 60Hz 0-10V	
LED life time	> 60000h - L80 - B20 (Ta 25°C)	
Color	White - 11 / Grey - 16 / Aluminium - 21	

## **DESCRIPTION**

#### Construction

- Die-cast aluminium body and trim (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.

### **Electrical & Optics**

- Universal input voltage: 120-277V 50/60Hz.
- 0-10V dimming available.
- Driver protected against voltage surges up to 5kV.
- Wiring on removable galvanized steel tray.
- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- Reflector made of engineering plastic metalized in highvacuum.
- Screen made of 3/16" thermal-shock resistant tempered glass.

### Listings

- UL certified to U.S. and Canadian standards, suitable for wet locations (cULus mark).
- Rated IP66 per EN60598.
- Luminaire rated for -25°C minimum ambient temperature.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

### Installation

- Ceiling installation.
- Die-cast aluminium base (EN 47100) for anchoring with rawlplugs.
- Universal plate for mounting on standard junction boxes (accessory).
- Spacer for side-entry of conduits (accessory).
- Supplied with power cord (18AWG conductors).







## VERSIONS (Click on below link to configure your product)



## performance

Size:

5" 29/32

4" 11/32 5" 29/32

OPTICS













See accessories in the next page




## ADAPTER PLATE FOR INSTALLATION ON ELECTRICAL BOXES.

Arcluce Code

1099622X

Code Ref.



## **TECHNICAL INFORMATION**


Weight 1.1 lb

## BASE PLATE FOR WALL/CEILING APPLICATION FOR SIDE ENTRY OF POWER CABLE - WHITE

Arcluce Code

1099626X-11

Code Ref.



#### **TECHNICAL INFORMATION**


Color	White - 11
Weight	1.76 lb

## BASE PLATE FOR WALL/CEILING APPLICATION FOR SIDE ENTRY OF POWER CABLE - GREY, SIMILAR TO

(RAL 7024)

Arcluce Code 1099626X-16

Code Ref.



## **TECHNICAL INFORMATION**


Color	Grey - 16
Weight	1.76 lb

## BASE PLATE FOR WALL/CEILING APPLICATION FOR SIDE ENTRY OF POWER CABLE - ALUMINIUM (RAL 9005)

Arcluce Code

1099626X-21

Code Ref.



## **TECHNICAL INFORMATION**

Color	Aluminium - 21
Weight	1.76 lb