

# QUAD200 (Model)



## TECHNICAL INFORMATION

[IES Files](#)

<b>Watt</b>	37W – 38W
<b>Luminaire</b>	Up to 4050lm
<b>CCT</b>	3000K – 4000K
<b>CRI</b>	>80
<b>Wiring</b>	120-277V 60Hz / 0-10V, 120-277V 60Hz / DALI
<b>LED life time</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>Color</b>	Stainless Steel - 30

## DESCRIPTION

### Construction

- Die-cast aluminium body (EN 47100).
- AISI 316L stainless steel trim.
- Die-cast aluminium control gear box (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.

### Electrical & Optics

- 0-10V dimming available.
- Driver protected against voltage surges up to 6kV.
- Wiring on removable galvanized steel tray.
- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- PMMA lenses for LEDs.
- Screen made of 13/32" thermal-shock resistant tempered glass.

### Listings

- UL certified to U.S. and Canadian standards, suitable for wet locations (cULus mark).
- Rated IP67 per EN60598.
- Luminaire rated for -40°C minimum ambient temperature.
- 1000-1500Kg static load capacity per EN60598.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.


### Installation

- Recessed installation.
- Supplied with galvanized and painted steel recessed installation box.
- Supplied with power cord (18AWG conductors).

IP67




## VERSIONS *(Click on below link to configure your product)*



[flush trim - recessed L box](#)

Size:

- 6" 23/32
- 13" 3/8
- 8" 11/16



[flush trim - recessed deep box](#)

Size:

- 11" 11/32
- 7" 15/16
- 8" 11/16



[trim above the ground - recessed L box](#)

Size:

- 6" 9/16
- 13" 3/8
- 9" 1/16



[trim above the ground - recessed deep box](#)

Size:


- 11" 3/16
- 7" 15/16
- 9" 1/16

## OPTICS




See accessories in the next page

## ANTI-SLIP OPAL GLASS.

Arcluce Code **1099280X**Code Ref. **O6599****TECHNICAL INFORMATION****Weight** 1.54 lb


---

## "L-SHAPED" ZINC-COATED STEEL INSTALLATION-BOX.

Arcluce Code **1099234X**Code Ref. **O6597****TECHNICAL INFORMATION****Weight** 3.53 lb


---

## ZINC-COATED STEEL INSTALLATION-BOX (LONG).

Arcluce Code **1099232X**Code Ref. **O6598****TECHNICAL INFORMATION****Weight** 3.31 lb

---


## "L-SHAPED" ZINC-COATED STEEL INSTALLATION-BOX WITH AISI 316L STAINLESS STEEL EDGE.

Arcluce Code **1099034X**Code Ref. **O6594****TECHNICAL INFORMATION****Weight** 3.53 lb

---

ZINC-COATED STEEL INSTALLATION-BOX (LONG) WITH AISI 316L STAINLESS STEEL EDGE.

Arcluce Code **1099035X**  
Code Ref. **O6595**



**TECHNICAL INFORMATION**

**Weight** 3.31 lb

---