

# **QUAD200** (Model)



TECHNICAL INFORMATION		<u>IES Files</u>
Watt	37W – 38W	
Luminaire	Up to 4050lm	
ССТ	3000K – 4000K	
CRI	>80	
Wiring	120-277V 60Hz / DALI, 120-277V 60Hz / 0-10V	
LED life time	> 60000h - L80 - B20 (Ta 25°C)	
Color	Stainless Steel - 30	

#### **DESCRIPTION**

#### Construction

- Die-cast aluminium body (EN 47100).
- AISI 316L stainless steel trim.
- Die-cast aluminium control gear box (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.

### **Electrical & Optics**

- 0-10V dimming available.
- Driver protected against voltage surges up to 6kV.
- Wiring on removable galvanized steel tray.
- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- PMMA lenses for LEDs.
- Screen made of 13/32" thermal-shock resistant tempered glass.

#### Listings

- UL certified to U.S. and Canadian standards, suitable for wet locations (cULus mark).
- Rated IP67 per EN60598.
- Luminaire rated for -40°C minimum ambient temperature.
- 1000-1500Kg static load capacity per EN60598.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

#### Installation

- Recessed installation.
- Supplied with galvanized and painted steel recessed installation box.
- Supplied with power cord (18AWG conductors).













## VERSIONS (Click on below link to configure your product)



flush trim - recessed L box

Size:

6" 23/32	
13" 3/8	
8" 11/16	



flush trim - recessed deep box

Size:

11" 11/32 7" 15/16 8" 11/16



trim above the ground - recessed L box

Size:

6" 9/16	
13" 3/8	
9" 1/16	



trim above the ground - recessed deep box

Size:

11" 3/16 7" 15/16 9" 1/16

## **OPTICS**











See accessories in the next page



## ANTI-SLIP OPAL GLASS.

Arcluce Code

1099280X

Code Ref.



#### **TECHNICAL INFORMATION**

Weight 1.54 lb

## "L-SHAPED" ZINC-COATED STEEL INSTALLATION-BOX WITH AISI 316L STAINLESS STEEL EDGE.

Arcluce Code

1099034X

Code Ref.



#### **TECHNICAL INFORMATION**

Weight 3.53 lb

## ZINC-COATED STEEL INSTALLATION-BOX (LONG) WITH AISI 316L STAINLESS STEEL EDGE.

Arcluce Code

1099035X

Code Ref.



## **TECHNICAL INFORMATION**

Weight 3.31 lb

#### "L-SHAPED" ZINC-COATED STEEL INSTALLATION-BOX.

Arcluce Code

1099234X

Code Ref.



## TECHNICAL INFORMATION

Weight 3.53 lb



## ZINC-COATED STEEL INSTALLATION-BOX (LONG).

Arcluce Code

1099232X

Code Ref.



#### **TECHNICAL INFORMATION**

Weight 3.31 lb