

RAY110 short (Model)



TECHNICAL INFORMATION


[IES Files](#) ↓

Watt	4W
Luminaire	Up to 575lm
CCT	3000K – RGBW
CRI	>80
Wiring	
LED life time	> 60000h - L80 - B20 (Ta 25°C)
Color	Aluminium - 21 / Stainless Steel - 30 / White - 11

DESCRIPTION



VERSIONS *(Click on below link to configure your product)*



[round trim stainless steel](#)

Size:
Ø 4" 11/16
2" 11/16

[squared trim stainless steel](#)

Size:
Ø 4" 23/32
2" 11/16

[die-cast aluminium trim](#)

Size:
Ø 4" 23/32
2" 11/16




OPTICS



See accessories in the next page

JUNCTION BOX IP68 - 4 WAYS - 2/3 POLES.

Arcluce Code **1099259X**
Code Ref.



TECHNICAL INFORMATION

Weight 0.11 lb

IP68 LINEAR JOINT - 2 WAYS - 2 POLES.

Arcluce Code **1099408X**
Code Ref.



TECHNICAL INFORMATION

Weight 0.07 lb

JUNCTION BOX IP68 - 4 WAYS - 4/5 POLES.

Arcluce Code **1099407X**
Code Ref.



TECHNICAL INFORMATION

Weight 0.18 lb

Arcluce Code **1098009X**
Code Ref.



TECHNICAL INFORMATION

Weight 1.1 lb

Arcluce Code **1098010X**
Code Ref.



TECHNICAL INFORMATION

Weight 1.1 lb
