

THUNDER110 (Model)



TECHNICAL INFORMATION

[IES Files](#) 

Watt	0.4W – 4W
Luminaire	Up to 575lm
CCT	3000K – RGBW
CRI	>80
Wiring	
LED life time	> 60000h - L80 - B20 (Ta 25°C)
Color	Stainless Steel - 30

DESCRIPTION




VERSIONS *(Click on below link to configure your product)*



[squared trim stainless steel](#)

Size:

- 2" 29/32
- 4" 11/32
- 4" 23/32



[stainless steel round trim](#)

Size:

- Ø 4" 23/32
- 2" 29/32
- 4" 11/32




OPTICS



See accessories in the next page

THERMOPLASTIC MATERIAL RECESSED INSTALLATION BOX.

Arcluce Code **1099236X**
Code Ref.




TECHNICAL INFORMATION

Weight 0.15 lb

JUNCTION BOX IP68 - 4 WAYS - 2/3 POLES.

Arcluce Code **1099259X**
Code Ref.



TECHNICAL INFORMATION

Weight 0.11 lb

Arcluce Code **1098009X**
Code Ref.



TECHNICAL INFORMATION

Weight 1.1 lb

Arcluce Code **1098010X**
Code Ref.



TECHNICAL INFORMATION

Weight 1.1 lb
