

THUNDER65 (Model)




TECHNICAL INFORMATION		IES Files 
Watt	0.4W	
Luminaire	Up to 10lm	
CCT	3000K – 4000K	
CRI	>80	
Wiring		
LED life time	> 60000h - L80 - B20 (Ta 25°C)	
Color	Stainless Steel - 30 / White - 11 / Aluminium - 21 / Grey - 16 / Satinised nickel - 33	

DESCRIPTION



VERSIONS *(Click on below link to configure your product)*



[squared trim stainless steel](#)

Size:

2" 15/32

2" 15/16




[stainless steel round trim](#)

Size:

Ø 2" 15/16

2" 15/32



[die-cast aluminium round trim](#)

Size:

Ø 2" 15/16

2" 15/32



[rectangular trim - die-cast aluminium](#)

Size:

Ø 4" 23/32

2" 3/4

1" 5/8



OPTICS



See accessories in the next page

THERMOPLASTIC MATERIAL RECESSED INSTALLATION BOX.

Arcluce Code **1099267X**
Code Ref.




TECHNICAL INFORMATION

Weight 0.07 lb

JUNCTION BOX IP68 - 4 WAYS - 2/3 POLES.

Arcluce Code **1099259X**
Code Ref.



TECHNICAL INFORMATION

Weight 0.11 lb

IP68 LINEAR JOINT - 2 WAYS - 2 POLES.

Arcluce Code **1099408X**
Code Ref.




TECHNICAL INFORMATION

Weight 0.07 lb

THERMOPLASTIC MATERIAL RECESSED INSTALLATION BOX.

Arcluce Code **1099214X**
Code Ref.



TECHNICAL INFORMATION

Weight 0.07 lb
