

TITO25 (Model)



TECHNICAL INFORMATION		<u>IES Files</u>
Watt	2W	
Luminaire	Up to 225lm	
ССТ	3000K – 4000K	
CRI	>80	
Wiring	700mA	
LED life time	> 60000h - L80 - B20 (Ta 25°C)	
Color	Stainless Steel - 30	

DESCRIPTION

Construction

- AISI 316L stainless steel body and trim.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.

Electrical & Optics

- To be operated only with constant current 700mA Class 2 remote drivers (order separately).
- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- PMMA lenses for LEDs.
- Clear PMMA screen.

Listings

- UL certified to U.S. and Canadian standards, suitable for wet locations (cULus mark).
- Rated IP68 per EN60598.
- Luminaire rated for -40°C minimum ambient temperature.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Surface installation.
- AISI 316L stainless steel bracket.
- Supplied with power cord. 22AWG conductors.









VERSIONS (Click on below link to configure your product)



tito25

Size: Ø 0" 31/32 2" 1/4 3" 1/32

OPTICS









See accessories in the next page




AISI 316L STAINLESS STEEL PEG.

Arcluce Code

1099256X

Code Ref.



TECHNICAL INFORMATION

0.18 lb Weight

PAINTED AISI 316L STAINLESS-STEEL SLOPED VISOR.

Arcluce Code

1099340X-12

Code Ref.



TECHNICAL INFORMATION

Color	Black - 12
Weight	0.11 lb

AISI 316L STAINLESS-STEEL SLOPED VISOR.

Arcluce Code

1099376X-30

Code Ref.



TECHNICAL INFORMATION


Stainless Steel - 30 Color Weight 0.11 lb

THERMOPLASTIC MATERIAL PEG.

Arcluce Code

1099257X

Code Ref.



TECHNICAL INFORMATION

Weight 0.11 lb