

# TITO25 (Model)



## TECHNICAL INFORMATION

<b>Watt</b>	2W
<b>Luminaire</b>	Up to 200lm
<b>CCT</b>	3000K – 4000K
<b>CRI</b>	>80
<b>Wiring</b>	700mA
<b>LED life time</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>Color</b>	Stainless Steel - 30

## DESCRIPTION

### Construction

- AISI 316L stainless steel body and trim.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.

### Electrical & Optics

- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- PMMA lenses for LEDs.
- Clear PMMA screen.
- To be operated only with constant voltage 24Vdc Class 2 remote drivers (order separately).

### Listings

- UL certified to U.S. and Canadian standards, suitable for wet locations (cULus mark).
- Rated IP68 (up to 3') per EN60598.
- Luminaire rated for -40°C minimum ambient temperature.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

### Installation

- Surface installation.
- AISI 316L stainless steel bracket.
- Supplied with power cord. 22AWG conductors.

IP68  
40"



## VERSIONS *(Click on below link to configure your product)*



[tito25](#)

Size:

Ø 0" 31/32

2" 1/4

3" 1/32


## OPTICS



See accessories in the next page

## AISI 316L STAINLESS STEEL PEG.

Arcluce Code **1099256X**  
Code Ref. **W9070**

**TECHNICAL INFORMATION**

**Weight** 0.18 lb

---

## PAINTED AISI 316L STAINLESS-STEEL SLOPED VISOR.

Arcluce Code **1099340X-12**  
Code Ref. **W9075-12**

**TECHNICAL INFORMATION**

**Color** Black - 12

---

**Weight** 0.11 lb

---

## AISI 316L STAINLESS-STEEL SLOPED VISOR.

Arcluce Code **1099376X-30**  
Code Ref. **W9075-30**

**TECHNICAL INFORMATION**

**Color** Stainless Steel - 30


---

**Weight** 0.11 lb

---

## THERMOPLASTIC MATERIAL PEG.

Arcluce Code **1099257X**  
Code Ref. **W9970**

**TECHNICAL INFORMATION**

**Weight** 0.11 lb

---