

# TITO55 (Model)



## TECHNICAL INFORMATION

[IES Files](#) 

|                      |                                |
|----------------------|--------------------------------|
| <b>Watt</b>          | 4W                             |
| <b>Luminaire</b>     | Up to 450lm                    |
| <b>CCT</b>           | 3000K – 4000K                  |
| <b>CRI</b>           | >80                            |
| <b>Wiring</b>        | 350mA                          |
| <b>LED life time</b> | > 60000h - L80 - B20 (Ta 25°C) |
| <b>Color</b>         | Stainless Steel - 30           |

## DESCRIPTION

### Construction

- AISI 316L stainless steel body and trim.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.

### Electrical & Optics

- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- PMMA lenses for LEDs.
- Screen made of 3/16" thermal-shock resistant tempered glass.
- To be operated only with constant current 350mA Class 2 remote drivers (order separately).

### Listings

- UL certified to U.S. and Canadian standards, suitable for wet locations (cULus mark).
- Rated IP68 per EN60598.
- Luminaire rated for -40°C minimum ambient temperature.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

### Installation

- Surface installation.
- AISI 316L stainless steel bracket.
- Supplied with power cord. 22AWG conductors.

**IP68**  
40"


## VERSIONS *(Click on below link to configure your product)*


[tito55](#)

Size:

Ø 2" 5/32

3" 21/32

3" 3/16

## OPTICS



See accessories in the next page

PAINTED AISI 316L STAINLESS-STEEL SLOPED VISOR.

Arcluce Code **1099019X-12**

Code Ref.



**TECHNICAL INFORMATION**

**Color** Black - 12

---

**Weight** 0.33 lb

---

AISI 316L STAINLESS-STEEL SLOPED VISOR.

Arcluce Code **1099319X-30**

Code Ref.



**TECHNICAL INFORMATION**

**Color** Stainless Steel - 30

---

**Weight** 0.33 lb

---