

# TULA (Model)



TECHNICAL INFORMATION		<u>IES Files</u> ↓
Watt	5W – 10W	
Luminaire	Up to 900lm	
ССТ	3000K – 4000K	
CRI	>80	
Wiring	120V 60Hz	
LED life time	> 60000h - L80 - B20 (Ta 25°C)	
Color	Grey - 16 / Aluminium - 21	

#### **DESCRIPTION**

#### Construction

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.

#### **Electrical & Optics**

- Wiring on removable galvanized steel tray.
- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- PMMA lenses for LEDs.
- Opal PMMA screen or 3/16" thermal-shock resistant tempered safety glass.

#### Listings

- UL certified to U.S. and Canadian standards, suitable for wet locations (cULus mark).
- Rated IP66 per EN60598.
- Luminaire rated for -25°C minimum ambient temperature.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

#### Installation

- Wall mounted.
- Waterproof grommet for single cable entry.
- Die-cast aluminium base (EN 47100) for anchoring with rawlplugs.
- Available accessory for mounting on standard junction boxes.











## VERSIONS (Click on below link to configure your product)



oneway

Ø 1" 31/32 4" 3/4 4" 19/32



oneway - opal

Ø 1" 31/32 4" 3/4 5" 7/16



twoway

Ø 1" 31/32 4" 3/4 5" 5/32



twoway - opal

Ø 1" 31/32 4" 3/4 6" 7/8



twoway - opal + blade

Ø 1" 31/32 4" 3/4 6" 3/32

### **OPTICS**



























## WALL PLATE TULA ANTHRACITE

Arcluce Code X-TU-WPCUS-16
Code Ref. 1099379X-16US



## **TECHNICAL INFORMATION**

Color	Grey - 16
Weight	0.88 lb

## WALL PLATE TULA ALUMINIUM

Arcluce Code X-TU-WPCUS-21 Code Ref. 1099379X-21US



## **TECHNICAL INFORMATION**

Color	Aluminium - 21
Weight	0.88 lb