

# TULA Bollard (Model)



## TECHNICAL INFORMATION

[IES Files](#) ↓

<b>Watt</b>	5W – 10W
<b>Luminaire</b>	Up to 525lm
<b>CCT</b>	3000K – 4000K
<b>CRI</b>	>80
<b>Wiring</b>	
<b>LED life time</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>Color</b>	Grey - 16 / Aluminium - 21

## DESCRIPTION



## VERSIONS *(Click on below link to configure your product)*



[comfort](#)


[performance](#)

Size:  
5" 7/16  
6" 13/32  
23" 5/8 to 35" 7/16

Size:  
4" 19/32  
6" 13/32  
23" 5/8 to 35" 7/16



## OPTICS




See accessories in the next page

ZINC-COATED AND PAINTED STEEL BASE PLATE WITH ZINC-COATED STEEL STUD BOLTS. 130 MM HIGH.

Arcluce Code **1099397X-16**

Code Ref.



#### TECHNICAL INFORMATION

**Color** Grey - 16

**Weight** 0.88 lb

IP68 LINEAR JOINT - 2 WAYS - 3 POLES.

Arcluce Code **1099409X**

Code Ref.




#### TECHNICAL INFORMATION

**Weight** 0.07 lb

JUNCTION BOX IP68 - 4 WAYS - 2/3 POLES.

Arcluce Code **1099259X**

Code Ref. **O7932**




#### TECHNICAL INFORMATION

**Weight** 0.11 lb

GALVANIZED AND PAINTED STEEL BASE PLATE WITH GALVANIZED STEEL STUD BOLTS. 130 MM HIGH.

Arcluce Code **1099397X-21**

Code Ref.



#### TECHNICAL INFORMATION

**Color** Aluminium - 21

**Weight** 0.88 lb